

NOVEMBER 13, 2023

CLASS A

Asbestos Clearance Report

97 Links Avenue, Mount Maunganui

TIM NEIL

Commissioned by Asbestos Consultants NZ Ltd



Summary / Preliminary Check

Contractor Name	AR Plus	
Site Supervisor	William Brown	
Friability of ACM	Friable	
Product that has bee	n removed	Textured coating
Asbestos Removal Co	ontrol Plan and notification	Yes
Enclosure Intact and	Operational?	Yes
Negative Pressure Ur	nits Operational?	Yes
Hygiene facility prese	ent, clean and operational?	Yes
Removal supervisor of area is ready for visu	confirmed enclosure/work al inspection?	Yes



Visual Inspection

Amount of Material removed (total area)	80 m2
Access available to all areas?	YES
Viewing window available?	YES
All ACM removed / Is area free of all ACM?	YES
All visible debris in work area removed?	YES
Adjacent surfaces are free from debris and visible dust?	YES
Any transit routes / waste routes / skips / hygiene facilities free of visible asbestos, debris and waste?	YES
Area surrounding work area free of visible asbestos debris?	YES
Visual Inspection Passed	YES

Air Monitoring

Background and Clearance Air Monitoring Conducted	YES
Background and Clearance Air Monitoring Passed	YES

Reoccupation

Has the enclosure been removed correctly?	YES
Has all materials been removed from site and the area is clean?	YES
Were all ACM products in the scope removed?	YES
Can the area be reoccupied under normal conditions?	YES

Declaration

Result	PASS	Date	10/11/2023
Inspected By	Terry O'Keeffe	Assessor Signature	Reviewers Signature
Reviewed By:	Aaron O'Keeffe	1.11 11	
Approved By	Archie Britz	Mægk	Aura



Introduction

This report relates to a visual inspection and asbestos air monitoring for ACM (asbestoscontaining material) and ARF (Airborne respirable fibre) following the removal of friable asbestos from Complete house at 97 Links Avenue, Mount Maunganui.

We confirm that we have read and accepted the ARCP (Asbestos Removal Control Plan) and Worksafe Notification, and that we are happy with the methods outlined in the documentation that were carried out by AR Plus, who were contracted to conduct the removal works by the PCBU (Person Conducting a Business or Undertaking).

The aim of this report is to provide a comprehensive overview of the results of the visual inspection and asbestos air monitoring, including the background and clearance air monitoring, to confirm the premises are now free from asbestos following the removal of friable asbestos.

Pre-Check – Prior to any asbestos removal starting

Site visit pre removal

Prior to the removal of friable asbestos, our team conducted a thorough precheck to ensure the safety of everyone involved. We visited the site on 07/11/2023 and checked the integrity of the enclosure, conducted a smoke test to ensure that the negative pressure unit was able to remove the smoke in time, and performed an Omni guard check to ensure that the negative pressure was correct. In addition, we left an asbestos air monitor at the decontamination entry door to ensure the air quality remained safe throughout the removal process.

Four Stage Clearance

Stage 1: Preliminary check

We conducted an initial assessment of the site's condition and degree of completion on 07/11/2023.

Stage 2: Inside the enclosure

A comprehensive visual inspection was conducted within the enclosure and/or work area to ensure thoroughness on 07/11/2023.

Stage 3: Air Monitoring

To ensure that airborne fibres were below trace levels, we conducted clearance air monitoring. This monitoring was essential to detect any invisible asbestos particles. Following the completion of air monitoring, we took swab samples in the removal area and decontamination unit on 07/11/2023

Stage 4: Enclosure dismantled

We conducted a final assessment of the work area after the removal contractors dismantled the enclosure on 10/11/2023, to verify that there was no contamination behind the enclosure post removal.



Methodology for clearance air monitoring/swab testing

The clearance air monitoring was completed using the following procedures:

1. Asbestos Air Monitoring

- a) Equipment setup: Set up the air monitoring equipment, including the air sampling pump, filter cassette and flow meter.
- b) Area selection: Identify the areas where the asbestos is likely to be present and select the sampling locations accordingly.
- c) Sampling duration: Run the air sampling pump for the desired duration, usually 1-8 hours.
- d) Record keeping: Record the duration of sampling, the location of the sampling point, and any other relevant information.
- e) Double Bag, each air sample separately and label accordingly.
- f) Sample analysis: Send the filter cassette to an IANZ approved laboratory for the analysis to determine the concentration of asbestos fibre in the air sample.
- g) Reporting: Report the findings and provide recommendations for any necessary remediation or additional monitoring.

2. Swab Sampling

- a) Equipment setup: Set up the sampling equipment, including the swabs, gloves, and personal protective equipment.
- b) Area selection: Identify the areas where the asbestos is likely to be present and select the sampling locations accordingly.
- c) Swab collection: Collect the swab samples by wiping the surface with a tape or ghost wetted swab to ensure that any asbestos fibres are captured.
- d) Record keeping: Record the location of the sampling point, the type of surface sampled, and any other relevant information.
- e) Double Bag, each swab sample separately and label accordingly.
- f) Sample analysis: Send the swab samples to an IANZ approved laboratory for the analysis to determine the presence of asbestos fibres.
- g) Reporting: Report the findings and provide recommendations for any necessary remediation or additional monitoring.

Laboratory testing

All testing is carried out by third party approved IANZ accredited laboratory which is Eurofins and uses the latest low powered stereo microscopy and polarized light microscopy techniques. This ensures that the results of the analyses are accurate and reliable. The testing services are designed to identify the exact composition of fibres in the sample, which can provide valuable insight into the health of the environment and the nature of the sample itself. This information can then be used to inform decisions about how to best manage the environment, or to understand the nature of a particular sample.



Laboratory analysis results

Location	Sample Type	Date	Sample	Respiratory	Result
			Number	Fibre Count	
Decon entry	Background	10/11/2023	1	1.5	PASS
Lounge	Clearance	10/11/2023	2	1	PASS
Hallway	Clearance	10/11/2023	3	3.5	PASS
Decon / enclosure	Surface Swab	10/11/2023	4	NAD	PASS
Composite ceiling	Surface Swab	10/11/2023	5	NAD	PASS

Summary

Our Asbestos clearance air monitoring returned an ARF (asbestos respirable fibre) level of <0.01 fibres/ml, which is below the recommended detection limit for ARF. Additionally, all swab tests taken returned readings with no asbestos detected.

Based on our reliance of the laboratory analysis, and as far as can be determined, 97 Links Avenue, Mount Maunganui-from where the friable asbestos was removed does not pose any risk to health and safety from exposure to asbestos.

As a competent person with BOHS qualifications IP402 and IP404, I confirm I can conduct asbestos air monitoring, assessments, sampling, surveying and write recommendations according to regulations.

Disclaimer

The inspection report provided by Asbestos Consultants NZ ltd is for the scope of the ACM (asbestos containing material) removal area only. It is the responsibility of the Asbestos Removal Contractor to ensure all ACMs are classified correctly and that the Worksafe Notices and Asbestos Removal Control Plans (ARCP's) are accurately reflected.

Asbestos Consultants NZ Ltd is not responsible for any errors or omissions in the classification of ACM's or in the content of any Worksafe Notices or ARCP's.

Reports and recommendations detailed in our inspection reports are subject to Asbestos Consultants NZ Ltd standard terms and conditions of trade services.

Furthermore, this inspection report is for the sole use of Tim Neil and their intended recipient. Under no circumstances may it be reproduced or used for any other purpose without written consent from Asbestos Consultants NZ Ltd.



The assessment and this report were completed by:



P. 0800 030 818 | Direct. 07 571 3941 | Office. 07 575 8880 | M. 027 223 4222

E. terry@asbestosconsultants.co.nz | W. www.asbestosconsultants.co.nz

Unit 5, 339 Matakokiri Drive, Tauriko, Tauranga




Company Director Asbestos Surveyor/Assessor - AA18010016 BOHS IP402 and IP404











Please consider the environment before printing this email





AIRBORNE FIBRE CONCENTRATION

Client Asbestos Consultants NZ

Client Contact Terry O'Keefe/Aaron O'Keefe/Archie Britz

Phone Number 027 223 4222

Email results@asbestosconsultants.co.nz Address 5/335 Matakokiri Drive, Tauriko, Tauranga



IANZ# 1402

Certificate ID	M-05442	Date Sampled ²	07/11/2023
Samples Taken By ²	Terry O'Keefe/Aaron O'Keefe/Archie Britz	Date Sample(s) Received	08/11/2023
Project Reference ²	N/A	Date Sample(s) Analysed & Issued	08/11/2023
Site Address ²	97 Links Ave, Mount Maun	ganui	
Location Slides Counted	Eurofins Focus 1277a Can	neron Road, Gate Pa, Tauranga 3122	

Lab ID	Sample ID ²	Sample Location ²	Cowl No. ²	Sample ² Duration (min.)	Flow ² Rate (L/min.)	Volume ² Sampled (L)	No. Fibres (f)	No. Fields	Conc. f/mL
1	1	Background - Decon entry	644	480	1	480	1.5	100	<0.01
2	2	Clearance - Lounge	679	60	8	480	1	100	<0.01
3	3	Clearance - Hallway	763	60	8	480	3.5	100	<0.01

- All Fibre counting is in accordance with NOHSC:3003(2005) & Eurofins | Focus In-house method NPM-TP01.
- Flow Rate and sample Duration are client-supplied (outside the scope of our IANZ accreditation). The flow rate reported on this form is in L/min. Data provided and volume sampled by the client is indicated with superscript 2 and may impact the results
- Eurofins | Focus did not conduct any sampling, and the data presented are based on the samples submitted by the client.
- This certificate should be read in its entirety and shall not be reproduced except in full without written approval of the laboratory.

Opinions and interpretations expressed herein are outside the scope of Eurofins | Focus IANZ accreditation

Analytical Notes:

AIRBORN	E FIBRE CONC	ENTRATION RECORDS	
Laboratory Use Only:			
NPL Test Slide Number	NPL03	5 Sets of lines visible	YES
Stage Micrometer Number	SM04	Stage Micrometer Calibration Factor	1.0
Microscope Number	Microscope 10)	
Measured Graticule Diameter/µm	100		
Corrected Graticule Diameter/µm	100		
Microscope Checks Complete	Yes		

Version: QS9010_R2

Date Reported: 8/11/2023

Eurofins Environment Testing NZ LTD (Trading as Eurofins | Focus) 1277a Cameron Road, Gate Pa, Tauranga 3122 Aotearoa New Zealand NZBN 94 290 460 24954 Telephone: +64 9 525 0568

Page 1 of 2

Certificate ID: M-05442









AIRBORNE FIBRE CONCENTRATION

METHODOLOGY:

Asbestos Counting

Fibre counting is conducted in accordance with the National Occupational Health & Safety Commission Guidance Note on the Membrane Filter Method For Estimating Airborne Asbestos Fibres 2nd Edition, [NOHSC:3003(2005)] (MFM) and in-house method NPM-TP01. Unless specifically noted, analysis is undertaken by approved analysts at the base facility. Fibre counts (Fibres/fields) are covered by the facility's IANZ scope of accreditation. The requirements of the NATA Specific Accreditation Criteria, ISO/IEC 17025 Application Document Life Sciences - Annex, Asbestos sampling and testing,

Sample History

Where samples are submitted/analysed over several days, the last extraction date is reported.

Issued: March 2022, are realised.

If the date and time of sampling are not provided, the Laboratory will not be responsible for compromised results should testing be performed outside the recommended holding time. Client samples are disposed of 3 months after analysis.

Holding Time Description **Testing Site** Extracted Asbestos - NOHSC:3003 (2005) 08/11/2023 Tauranga Indefinite

Comments

Asbestos Counter/Identifier:

Liam Swanson

Analyst

Senior Analyst-Asbestos (Key Technical Personnel)

Final Report - This report replaces any previously issued Report

- Indicates Not Requested

Measurement uncertainty of test data is available on request, or please click here.

Eurofins shall not be liable for loss, cost, damages or expenses incurred by the client or any other person or company resulting from the use of any information or interpretation given in this report. In no case shall Eurofins be liable for consequential damages including, but not limited to, lost profits, damages for failure to meet deadlines and lost production arising from this report. This document shall not be reproduced except in full and relates only to the items tested. Unless indicated otherwise, the tests were performed on the samples as received.

Version: QS9010_R2

Eurofins Environment Testing NZ LTD (Trading as Eurofins | Focus)

Date Reported: 8/11/2023

1277a Cameron Road, Gate Pa, Tauranga 3122 Aotearoa New Zealand NZBN 94 290 460 24954 Telephone: +64 9 525 0568 Page 2 of 2

Certificate ID: M-05442







Client Asbestos Consultants NZ

Client Contact Terry O'Keefe/Aaron O'Keefe/Archie Britz

Phone Number 027 223 4222

Email results@asbestosconsultants.co.nz Address 5/335 Matakokiri Drive, Tauriko, Tauranga



Λ	NΙ	7#	4	A	0

Certificate ID	T-13015	Date Sampled ²	
Samples Taken By ²	Terry (07/11/23)	Date Sample(s) Received	08/11/2023
Project Reference ²	N/A	Date Sample(s) Analysed & Issued	8/11/2023
Site Address ²	97 Links Ave, Mount	Maunganui	
Location Sample Analysed	Eurofins Focus 1277	'a Cameron Road, Gate Pa, Tauranga 3	3122

Sample ID ²	Sample Details ²	Sample type	Sample size	Fibres Identified
4	Swab - Decon Enclosure	Swab	Sufficient	ORF, NAD
5	Swab - Composite Ceiling	Swab	Sufficient	ORF, NAD
	4 5			

Fibre Identification Key:			
*	See Analytical Notes	ORF	Organic Fibre
CHR	Chrysotile (White Asbestos)	SMF	Synthetic Mineral Fibre
AMO	Amosite (Brown / Grey Asbestos)	NFD	No Fibres Detected
CRO	Crocidolite – (Blue Asbestos)	NAD	No Asbestos Detected
UMF	Unknown Mineral Fibre		

Sample Size Guid	e:
Sufficient	Sample weight >1 g
Limited	Sample weight between 0.5 g -1 g
Insufficient	Sample weight <0.5 g; small size could misrepresent what is in sampled material. Suggest the client obtain a larger sample.

- Samples submitted have been analysed to determine the presence of asbestos using stereo microscopy followed by polarised light microscopy (PLM) and dispersion staining (DS) techniques as documented in AS 4964–2004 and in-house method NPM-TP03 for Qualitative Identification of Asbestos in Bulk Samples.
- Eurofins | Focus did not carry out any sampling, and the data presented are based on the samples submitted. Data supplied by the client is indicated with superscript 2 and may impact the results.
- This certificate should be read in its entirety and shall not be reproduced except in full without written approval of the laboratory.

Version: QS9011_R2

Date Reported: 8/11/2023

Eurofins Environment Testing NZ LTD (Trading as Eurofins | Focus) 1277a Cameron Road, Gate Pa, Tauranga 3122 Aotearoa New Zealand NZBN 94 290 460 24954 Telephone: +64 9 525 0568

Page 1 of 3 Certificate ID: T-13015





% 0800 030 818





Focus

Certificate of Analysis

Methodology

Asbestos Fibre Identification

Conducted in accordance with the Australian Standard AS 4964 - 2004: Method for the Qualitative Identification of Asbestos in Bulk Samples and in-house Method NPM - TP03 by polarised light microscopy (PLM) and dispersion staining (DS) techniques NOTE: Positive Trace Analysis results indicate the sample contains detectable respirable

Unknown Mineral

Mineral fibres of unknown type, as determined by PLM with DS, may require another analytical technique, such as Electron Microscopy, to confirm unequivocal identity NOTE: While Actinolite, Anthophyllite and Tremolite asbestos may be detected by PLM with DS, due to variability in the optical properties of these materials, AS 4964 – 2004 requires that these are reported as UMF unless confirmed by an independent technique. The whole sample submitted is first dried and then passed through a 10 mm sieve followed by a 2 mm sieve. All fibrous matter greater than 10 mm greater than 2 mm and the

Subsampling Soil Samples

material passing through the 2 mm sieve are retained and analysed for the presence of asbestos. If the sub 2 mm fraction is greater than approximately 30 g to 60g, then a subsampling routine based on ISO 3082:2009(E) is employed.

NOTE: Depending on the nature and size of the soil sample, the sub-2 mm residue material may need to be subsampled for trace analysis in accordance with AS 4964

fibres

Bonded asbestos containing material (ACM)

The material is first examined, and any fibres are isolated for identification by PLM and DS. Where required, interfering matrices may be removed by disintegration using a range of heat, chemical or physical treatments, possibly combined. The resultant material is then further examined in accordance with AS 4964 - 2004.

NOTE: Even after disintegration, it may be difficult to detect the presence of asbestos in some asbestos-containing bulk materials using PLM and DS. This is due to the low grade or small length or diameter of the asbestos fibres present in the material or to the fact that very fine fibres have been distributed intimately throughout the materials. Vinyl/asbestos floor tiles, some asbestos-containing sealants and mastics, asbestos-containing epoxy resins and some ore samples are examples of these types of material, which are difficult to

Limit of Reporting

The performance limitation of the AS 4964 - 2004 method for non-homogeneous samples is 0.1 g/kg (equivalent to 0.01% (w/w)). Where no asbestos is found by PLM and DS, including Trace Analysis, this is considered at the nominal reporting limit of 0.01% (w/w) The National Environment Protection (Assessment of Site Contamination) Measure 1999 (NEPM) screening level of 0.001% (w/w) is intended as an on-site determination, not a laboratory Limit of Reporting (LOR), per se. Examination of a large sample size (e.g., 500 mL) may improve the likelihood of detecting asbestos, particularly Asbestos Fines

(AF), to aid assessment against the NEPM criteria.

Sample History

Where samples are submitted/analysed over several days, the last extraction date is reported. If the date and time of sampling are not provided, the Laboratory will not be responsible for compromised results should testing be performed outside the recommended holding time. Client samples are disposed of 3 months after analysis.

Description AS4964-2004 and in-house Method NPM - TP03

Testing Site Tauranga

Extracted

Holding Time Indefinite

Version: QS9011 R2

Date Reported: 8/11/2023

Eurofins Environment Testing NZ LTD (Trading as Eurofins | Focus) 1277a Cameron Road, Gate Pa, Tauranga 3122

Aotearoa New Zealand NZBN 94 290 460 24954 Telephone: +64 9 525 0568

Page 2 of 3 Certificate ID: T-13015









Comments

Asbestos Counter/Identifier:

Liam Swanson

Analyst

Holly Nordstrom

Senior Analyst-Asbestos (Key Technical Personnel)

Final Report - this report replaces any previously issued Report

- Indicates Not Requested

Measurement uncertainty of test data is available on request or please click here.

Eurofins shall not be liable for loss, cost, damages or expenses incurred by the client or any other person or company resulting from the use of any information or interpretation given in this report. In no case shall Eurofins be liable for consequential damages including, but not limited to, lost profits, damages for failure to meet deadlines and lost production arising from this report. This document shall not be reproduced except in full and relates only to the items tested. Unless indicated otherwise, the tests were performed on the samples as received.

Version: QS9011_R2

Date Reported: 8/11/2023

Eurofins Environment Testing NZ LTD (Trading as Eurofins | Focus) 1277a Cameron Road, Gate Pa, Tauranga 3122 Aotearoa New Zealand NZBN 94 290 460 24954 Telephone: +64 9 525 0568

Page 3 of 3

Certificate ID: T-13015





% 0800 030 818



Photos from 97 Links Avenue



Exclusion zone



Enclosure



Enclosure



Enclosure



Enclosure



Enclosure





Smoke test



BAM at Decon entry



Removal complete



Removal complete



Removal complete



CAM in hallway





CAM in lounge



Enclosure removed



Enclosure removed



Enclosure removed



Enclosure removed



Enclosure removed



END OF REPORT



ASBESTOS CONSULTANTS NZ LTD 5/339 Matakokiri Drive **TAURIKO, 3112 NEW ZEALAND**